

Serie Standard Inverter • MSPEZ-*VJA ó YJA

PRESTACIONES



ALTURA 250 mm



PEAD-M*JA

NOVEDAD



SUZ-M35VA

NOVEDAD



SUZ-M50/60/71VA

NOVEDAD



PUZ-M100/125/140VKA/YKA

MODELO			MSPEZ-35VJA	MSPEZ-50VJA	MSPEZ-60VJA	MSPEZ-71VJA	MSPEZ-100VJA	MSPEZ-100YJA
Unidad interior			PEAD-M35JA	PEAD-M50JA	PEAD-M60JA	PEAD-M71JA	PEAD-M100JA	PEAD-M100JA
Unidad exterior			SUZ-M35VA	SUZ-M50VA	SUZ-M60VA	SUZ-M71VA	PUZ-M100VKA	PUZ-M100YKA
Capacidad	Frio Nominal (Min-Max)	kW	3,6 (0,8-3,9)	5,0 (1,7-5,6)	6,1 (1,6-6,3)	7,1 (2,2-8,1)	9,5 (4,0-10,6)	9,5 (4,0-10,6)
	Calor Nominal (Min-Max)	kW	4,1 (1,1-5,0)	6,0 (1,5-7,2)	7,0 (1,6-8,0)	8,0 (2,0-10,2)	11,2 (2,8-12,5)	11,2 (2,8-12,5)
Consumo Nominal	Frio	kW	0,92	1,35	1,69	2,02	2,87	2,87
	Calor	kW	1,02	1,46	1,84	2,15	2,94	2,94
Consumo eléctrico anual*	Frio	kWh/año	217	287	353	428	613	613
	Calor	kWh/año	931	1.430	1.594	2.080	2.795	2.795
Coeficiente energético	EER / COP		3,90 / 4,00	3,70 / 4,10	3,60 / 3,80	3,50 / 3,71	3,30 / 3,80	3,30 / 3,80
	SEER (Etiqueta)		5,8 (A+)	6,1 (A++)	6,0 (A+)	5,8 (A+)	5,4 (A)	5,4 (A)
	SCOP (Etiqueta)*		3,9 (A)	4,2 (A+)	4 (A+)	3,9 (A)	4,0 (A+)	4,0 (A+)
	Caudal de aire (B/M/A)	m³/min	10,0 / 12,0 / 14,0	12,0 / 14,5 / 17,0	14,5 / 18,0 / 21,0	17,5 / 21,0 / 25,0	24,0 / 29,0 / 34,0	24,0 / 29,0 / 34,0
Unidad Interior	Presión Estática	Pa	35 / 50 / 70 / 100 / 150	35 / 50 / 70 / 100 / 150	35 / 50 / 70 / 100 / 150	35 / 50 / 70 / 100 / 150	35 / 50 / 70 / 100 / 150	35 / 50 / 70 / 100 / 150
	Nivel sonoro (B/M/A)	dB(A)	23 / 27 / 30	26 / 31 / 35	25 / 29 / 33	26 / 30 / 34	29 / 34 / 38	29 / 34 / 38
	Potencia sonora	dB(A)	54	59	55	58	62	62
	Dimensiones al x an x fon	mm	250 x 900 x 732	250 x 900 x 732	250 x 1.100 x 732	250 x 1.100 x 732	250 x 1.400 x 732	250 x 1.400 x 732
Unidad Exterior	Peso	kg	26	27	30	30	39	39
	Caudal de aire	m³/min	34,3	45,8	50,1	50,1	79	79
	Nivel sonoro	dB(A)	48	48	49	49	51	51
	Potencia sonora	dB(A)	59	64	65	66	70	70
Unidad Exterior	Dimensiones al x an x fon	mm	550 x 800 x 285	714 x 800 x 285	880 x 840 x 330	880 x 840 x 330	981 x 1.050 x 330	981 x 1.050 x 330 (+40)
	Peso	kg	35	41	54	55	76	78
	Refrigerante R32	Pre-carga kg / PCA / TCO² eq	0,90 / 675 / 0,61	1,20 / 675 / 0,81	1,25 / 675 / 0,84	1,45 / 675 / 0,98	3,10 / 675 / 2,09	3,10 / 675 / 2,09
	Tensión/Fases - Intensidad Máxima	V/F - A	230/1 - 9,6	230/1 - 14,9	230/1 - 16,4	230/1 - 16,8	230/1 - 22,7	400/3 - 14,2
Diám. tuberías líquido/gas		mm	6,35 / 9,52	6,35 / 12,7	6,35 / 15,88	9,52 / 15,88	9,52 / 15,88	9,52 / 15,88
Long. Máx. tubería vert/total		m	12 / 20	30 / 30	30 / 30	30 / 30	30 / 55	30 / 55
Rango de operación	Tª exterior para refrigeración	°C	-10 ~ +46	-15 ~ +46	-15 ~ +46	-15 ~ +46	-15 ~ +46	-15 ~ +46
	Tª exterior para calefacción	°C	-10 ~ +24	-10 ~ +24	-10 ~ +24	-10 ~ +24	-15 ~ +21	-15 ~ +21