



Gama **Mr.Slim** Split 1x1 **Conductos**



Serie S • MSEZ-*VA



PRESTACIONES



MODELO			MSEZ-25VA	MSEZ-35VA	MSEZ-50VA	MSEZ-60VA	MSEZ-71VA
Unidad interior			SEZ-M25DA	SEZ-M35DA	SEZ-M50DA	SEZ-M60DA	SEZ-M71DA
Unidad exterior			SUZ-M25VA	SUZ-M35VA	SUZ-M50VA	SUZ-M60VA	SUZ-M71VA
Capacidad	Frío Nominal (Mín-Máx)	kW	2,5 (1,4-3,2)	3,5 (0,7-3,9)	5,0 (1,1-5,6)	6,1 (1,6-6,3)	7,1 (2,2-8,1)
	Calor Nominal (Mín-Máx)	kW	2,9 (1,3-4,2)	4,2 (1,1-5,0)	6,0 (1,5-7,2)	7,4 (1,6-8,0)	8,0 (2,0-10,2)
Consumo Nominal	Frío	kW	0,71	1	1,54	1,84	2,15
	Calor	kW	0,8	1,07	1,61	2,04	2,28
Consumo eléctrico anual*	Frío	kWh/año	165	207	290	386	452
	Calor	kWh/año	807	884	1.499	1.525	2.072
Coeficiente energético	EER / COP		3,50 / 3,61	3,50 / 3,90	3,23 / 3,71	3,30 / 3,61	3,30 / 3,50
	SEER (Etiqueta)		5,3 (A)	5,9 (A+)	6,0 (A+)	5,5 (A)	5,5 (A)
	SCOP (Etiqueta)*		3,8 (A)	4,1 (A+)	4,0 (A)	4,2 (A+)	3,9 (A)
Unidad Interior	Caudal de aire (B/M/A)	m³/min	6/7/9	7/9/11	10/13/15	12/15/18	12/16/20
	Presión Estática	Pa	5/15/35/50	5/15/35/50	5/15/35/50	5/15/35/50	5/15/35/50
	Nivel sonoro (B/M/A)	dB(A)	22/25/29	23/28/33	29/33/36	29/33/37	29/34/39
	Potencia sonora	dB(A)	50	53	57	58	60
	Dimensiones al x an x fon	mm	200 x 790 x 700	200 x 990 x 700	200 x 990 x 700	200 x 1.190 x 700	200 x 1.190 x 700
	Peso	kg	18	21	23	27	27
	Caudal de aire	m³/min	36,3	34,3	45,8	50,1	50,1
Unidad Exterior	Nivel sonoro	dB(A)	45	48	48	49	49
	Potencia sonora	dB(A)	59	59	64	65	66
	Dimensiones al x an x fon	mm	550 x 800 x 285	550 x 800 x 285	714 x 800 x 285	880 x 840 x 330	880 x 840 x 330
	Peso	kg	30	35	41	54	55
	Refrigerante R32	Pre-carga kg / PCA / TCO ² eq	0,65 / 675 / 0,44	0,90 / 675 / 0,61	1,20 / 675 / 0,81	1,25 / 675 / 0,84	1,45 / 675 / 0,98
	Tensión/Fases - Intensidad Máxima	V/F - A	230/1 - 7,2	230/1 - 9,0	230/1 - 14,2	230/1 - 15,5	230/1 - 15,7
	Diám. tuberías líquido/gas	mm	6,35/9,52	6,35/9,52	6,35/12,7	6,35/15,88	9,52/15,88
Long. Máx. tubería vert/total		m	12/20	12/20	30/30	30/30	30/30
Rango de operación	Tª exterior para refrigeración	°C	-10 ~ +46	-10 ~ +46	-15 ~ +46	-15 ~ +46	-15 ~ +46
	Tª exterior para calefacción	°C	-10 ~ +24	-10 ~ +24	-10 ~ +24	-10 ~ +24	-10 ~ +24